



ATLANTIC® Gearmax-Syn DCT

Product Description

Dual-clutch transmissions (DCTs) are automatic transmissions based on the mechanism of manual transmissions. The complex system essentially consists of two manual transmissions in the same housing. As one clutch is engaged, the other readies the next appropriate gear, minimizing the interruption of power and improving performance and efficiency.

Atlantic Gearmax-Syn is a full synthetic transmission fluid for use in Dual Clutch Transmissions. It delivers maximum protection over wide operating temperatures and service conditions. Suitable for use in some models of Volkswagen, Audi, Skoda and other passenger vehicles featuring Dual Clutch Transmissions.

Features & Benefits

- High shear resistance – as a result the viscosity remains constant
- Exceptional clutch performance due to the frictional characteristics of the oil
- Excellent thermal and oxidation stability



Technical Specifications

Audi: VW TL 052 182 / VW TL 052 529	Ferrari: TF DCT-F3	Porsche: 999.917.080.00
BMW: 83 22 2 148 578, 83 22 2 148 579 / 83 22 0 440 214 & 83 22 2 147 477 (BMW DCTF-1)	Fiat: BOT 341	Renault: BOT 450
Citroen/Peugeot: 9734.S2	Ford/Nissan: M2C936A	Volkswagen/Skoda/Seat: VW TL 052 182
	Mercedes-Benz: MB 236.21 / MB 236.25	Volvo: 1161838, 1161839
	Mitsubishi: MZ320065 Dia-Queen SSTF-1	

PRODUCT TECHNICAL CHARACTERISTICS

Characteristics	Method	Test Result
Flash Point (COC)	°C	200
Pour Point	°C	-40
Viscosity @ 40°C	mm ² /s	34.5
Viscosity @ 100°C	mm ² /s	7.0
Specific Gravity @ 15°C	g/ml	0.84

Health and Safety

The product should not be used for purposes other than its intended use. Refer the recommendations provided on the MSDS.

Product code: TDCS000

All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2018 Atlantic Lubricants Pty Ltd. All rights reserved

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

QUEENSLAND

Unit 2
7-9 Tradelink Road
Hillcrest QLD 4118
Ph: (07) 3556 1235

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800