

Issue Date: November 2017

PRO DIESEL 15W-40 Semi Synthetic

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

Product Name

Pro Diesel CJ-4 Semi Synthetic

Product Code

DO-15W-40CJ-4

Product Use

Top Tier Heavy Duty Diesel Engine Oil

Company Name

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

Address

40 Liverpool Street
Ingleburn NSW 2565

Emergency Telephone:

(02) 9829 7555

Telephone Number/Fax

Tel: (02) 9829 7555 Fax: (02) 9829 4555

Other Information

Atlantic Technical Officer: Con Zikos (02) 9829 7555 Mobile 0425 366 367

2. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition

Severely refined petroleum distillates with performance additives.

<u>Ingredients Name</u>	<u>CAS</u>	<u>Proportion</u>
Ingredients determined not to be hazardous	Not required	100 %

3. HAZARDS IDENTIFICATION

OSHA/HCS status Classification of the substance or mixture This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Not classified.

GHS label elements



Hazard Pictograms

Signal word

Warning.

Hazard statements

Very toxic to aquatic life; harmful if swallowed.

Precautionary statements

Prevention

Avoid release to environment. Do not eat, drink or smoke when using product. Wash thoroughly after handling.

Response

Collect spillage. IF SWALLOWED: call the POISON CENTRE or doctor if you feel unwell.

Storage

Not applicable.

Disposal

Not applicable.

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

Atlantic Oils - SYDNEY 40 Liverpool Street Ingleburn NSW 2565 Ph: (02) 9829 7555 Fax: (02) 9829 4555	Atlantic Oils - QLD P.O. Box 1250 Slacks Creek QLD 4127 M: 0402 644 575	Atlantic Oils - VICTORIA 6A Nicholas Drive Dandenong South 3175 Ph: (03) 9768 3307 Fax: (03) 9768 2832	Atlantic Oils - NEWCASTLE 31 Old Punt Road Tomago NSW 2322 Ph: (02) 4964 8436	Atlantic Oils - DARWIN Unit 1B 894 Stuart Highway Pinelands NT 0829 M: 0477 200 567	Atlantic Oils - A.C.T. P.O. Box 733 Gungahlin ACT 2912 M: 0411 094 945	Atlantic Oils - Tasmania 42 - 44 Davenport Road Quoiba 7310 Ph: (03) 6424 8799
---	--	---	---	--	---	--

4. FIRST AID MEASURES

Inhalation

Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops and persists, seek medical attention.

Ingestion

DO NOT induce vomiting. Immediately wash out mouth with water. Seek medical attention.

Skin

Remove contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops, seek medical attention.

Eye

If contact with the eye(s) occurs, wash with copious amounts of water, holding eyelids(s) open. Take care not to rinse contaminated water into the non-affected eye. If irritation develops and persists, seek medical attention.

First Aid Facilities

Eye wash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing Media

Carbon dioxide, foam or dry chemical.

Do NOT use water jets. Cool fire exposed containers with water spray.

Specific Hazards

Combustible C2 liquid. Fire-exposed container may rupture/explode.

Hazardous

Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes including oxides of carbon.

Precautions in

connection with Fire

Self-Contained Breathing Apparatus (S.C.B.A) and full protective clothing should be worn to minimise exposure.

6. ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill. Place inert, non combustible, absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Corrosiveness

Not corrosive to aluminium.

Handling

Repeated or prolonged contact with this material should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking or going to the toilet. Build-up of mists in the working atmosphere must be prevented.

Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.

Storage

Combustible C2 liquid for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure Limits

No exposure standards have been established for this material by the National Occupational Health And Safety Commission (NOHSC).

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependent upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

Eye Protection

Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

Eng. Controls

Natural ventilation should be sufficient, however where vapours or mists are generated the use of a local exhaust ventilation system (drawing vapours/mists away from workers breathing zone) is recommended.

Other Information

No biological limit allocated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Amber coloured oily liquid.

Melting Point

Not available.

Boiling Point

Not available.

Solubility in Water

Insoluble

Specific Gravity

(H₂O=1)

Not Specified

pH Value

Not applicable

Vapour Pressure

Not applicable

Vapour Density

(Air=1)

Not applicable

Flash Point

222°C (Penskey Martens Closed Cup)

Flammability

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. Remove all sources of heat and ignition.

Ignition Temperature

Not available.

Flammable Limits LEL

Not available.

Flammable Limits UEL

Not available.

Kinematic Viscosity

106.4 cSt @ 40°C

14.8 cSt @ 100°C

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Hazardous

Polymerization

Will not occur.

Materials to Avoid

Strong oxidising agents.

Hazardous

Decomposition

Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Hazardous Reaction

Hazardous reaction with strong oxidising agents.

Conditions to Avoid

Heat, direct sunlight, open flames or other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data is available for this material.

Inhalation

May cause irritation to the mucous membrane and upper airways, where material is heated and is used in poorly ventilated areas. Symptoms may include headache, dizziness and nausea.

Ingestion

May cause irritation of the gastrointestinal system. Symptoms may include nausea, vomiting and diarrhoea.

Skin

May cause irritation in contact with the skin, which may result in redness and itchiness, possibly leading to dermatitis.

Eye

May cause irritation in contact with the eyes which could result in redness, stinging and tearing.

Chronic Effects

Prolonged or repeated contact with this material may result in skin irritation possibly leading to dermatitis.

12. ECOLOGICAL INFORMATION

No ecological data is available for this material.

Environ. Protection

Prevent this material from entering the environment.

Mobility

No data available for this specific product.

Persistence /

Degradability

No data available for this specific product.

Bioaccumulation

No data available for this specific product.

Ecotoxicity

No data available for this specific product.

13. DISPOSAL CONSIDERATIONS

Dispose of waste according to federal, E.P.A. and state regulations. Assure conformity with all applicable regulations.

14. TRANSPORT INFORMATION

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

U.N. Number

None Allocated

Proper Shipping Name

None Allocated **DG**

Class

None Allocated

Hazchem Code

None Allocated

Packing Group

None Allocated

15. REGULATORY INFORMATION

Poisons Schedule

Not Scheduled

16. OTHER INFORMATION

Contact Person/Point

For information concerning details on this Safety Data Sheet contact your local Technical Services Manager on the following number:
Atlantic Technical Help Line (02) 9829 7555

IMPORTANT DISCLAIMER

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Atlantic accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein. 24 HOUR EMERGENCY CONTACT (02) 9829 7555

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.