



PRODUCT DATA SHEET



ATLANTIC® SUPERMAX 15W-40 CH-4/SJ

Atlantic Supermax 15W-40CH-4/SJ is a high ash Multigrade Diesel Engine Oil formulated to meet the needs of older American, European and Japanese heavy-duty diesel engines. Atlantic Supermax 15W- 40CH-4/SJ meets the requirements of JASO DH-1 and also exceeds the soot thickening control and valve train wear protection requirements of API CH-4

Features & Benefits

- Very high viscosity index and a high resistance against shearing
- Lower fuel consumption
- Fast cold start properties which results in less wear due a stable lubricant film



Technical Specifications

SAE Viscosity: 15W-40	MAN: 271
API: CH-4/SJ	Mercedes Benz: 228.1
ACEA: E3	MTU: Type 1
CAT: ECF-1-a	Renault: RD, RD-2
Cummins: CES 20076	Volvo: VDS-2
Mack: EO-M Plus	ZF: TE-ML-07C

Product code: DSM1540

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800



PRODUCT DATA SHEET

Technical Specifications

Test	Typical Result
KV @ 100°C, cSt	12.4
KV @ 40°C, cSt	71.22
Viscosity Index	174
KV @ 100°C, cSt (after 20hr KRL shear)	7.1
KV @ 100°C, cSt (after 100hr KRL shear)	6.6
KV @ 40°C, cSt (after 100hr KRL shear)	39.1
BV @ -20°C cP	4770
CCS @ -20°C cP	3210
CCS @ -25°C cP	6070

The above data is typical and does not constitute a specification

Product code: FFP1030

All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2016 Atlantic Lubricants Pty Ltd. All rights reserved

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800