



PRODUCT DATA SHEET

ATLANTIC C1 5W-30

Product Description:

Atlantic C1 5W-30 is a full synthetic low S.A.P.S (Sulphated Ash, Phosphorus and Sulphur) high performance engine oil designed to help prolong the life and maintain the efficiency of exhaust emission reduction systems. Atlantic C1 5W-30 can be used in high performance passenger car & light duty Van, 4WD petrol & DI diesel vehicles and offers extended drain benefits as per manufacturer requirements. Atlantic C1 5W-30 can be used where the following specifications are required: ACEA C1, Ford M2C934-B or Jaguar Land Rover STJLR.03.5005.

Features and Benefits:

- Minimises engine emissions
- Maximises fuel efficiency
- Optimal wear protection
- Superior engine cleanliness
- Long drain interval suitability
- Offers advanced protection of Diesel Particulate Filters (DPF's)



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.846
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	57
Viscosity, Kinematic @100°C	ASTM D 445	cSt	10.4
Viscosity Index	ASTM D 2270	-	174
Total Base Number (TBN)	ASTM D 2896	mgKOH/g	6.8
Cold Cranking Viscosity @ -30°C	ASTM D 5293	cP	3980
Sulphated ash	ASTM D 5185	ppm	490
Zinc	ASTM D 5185	ppm	510
HTHS @ 150°C	-	cP	>2.9

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	PC105301
20 Litre	PC105302
60 Litre	PC105303
205 Litre	PC105304
1000 Litre	PC105305



Specifications/ Performance Levels:

- **SAE Viscosity:** 5W-30
- **ACEA:** C1
- **Ford:** WSS-M2C934-B
- **STJLR.03.5005**



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900