

**ENGINE FLUSH**

**Product Description:**

Envirotek Engine Flush is designed to be used for both petrol and diesel engines.

Even the best of oils breaks down with time. Once dirty oil is saturated with impurities it will turn to sludge. With today's extended service intervals combined with severe driving conditions, contamination free engines are essential for safe hassle-free motoring.

Sludge will negatively affect the power of the engine, cause excessive wear and tear on all moving parts, increase the running cost of the vehicle, and contribute to polluting exhaust emissions.

A normal oil change without Engine Flush will only get rid of the sludge the oil is currently carrying in suspension. This is the reason we recommend the use of Engine Flush on all services. Therefore, the new oil doesn't have to start cleaning the mess left behind from the previous old oil.

Clean oil for a clean engine.

**Features and Benefits:**

- Removes sludge and soft carbon built-up from engine.
- Clean and free noisy hydraulic lifters.
- Raise and stabilise compression by removing carbon.
- Keep new oil cleaner for longer.
- Improve engine efficiency providing more power.
- Lubricate and protect while cleaning.



**Dosage Rate:**

System Cleaner	Recommended Dosage Rate			Ratio
Vehicle Size	Small	Medium	Large	50 ml per 1 Litre Oil
Per Service	250ml	300ml	350ml	

DISTRIBUTED BY:

**ATLANTIC LUBRICANTS PTY LTD**

**HEAD OFFICE - SYDNEY**

40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**

P: (03) 9768 3307

**NEWCASTLE**

P: (02) 4964 8436

**ACT**

P: 0411 094 945

**QUEENSLAND**

P: (07) 3556 1235

**NORTHERN TERRITORY**

P: 0429 771 810

**TASMANIA**

P: (03) 6423 4900

**Direction For Use:**

Add Engine Flush to oil. Run engine for at least 10min. Drain oil while still hot, change filter and refill with new oil. This product contains a lubricant that protects against wear and tear during use. The lubricant allows the mechanic to take the vehicle on a test drive whilst the Engine Flush is cleaning.

Engine Flush is safe for use in all vehicles fitted with both DPF or PPE. It is important to drain the old oil containing the Engine Flush whilst the oil is still hot. Don't let the old oil cool down as the old may be carrying excessive amount of sludge which can solidify in the sump. **DRAIN OIL STRAIGHT AFTER FLUSHING.**

Waste oil after flushing is still perfectly suitable for collection and recycling by waste oil companies. For extreme scenarios where heavy sludge due to serious lack of servicing, please call our technical line on 0490 072 548.

All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2023 Envirotek International Pty Ltd.

24 April 2023

DISTRIBUTED BY:

**ATLANTIC LUBRICANTS PTY LTD**

**HEAD OFFICE - SYDNEY**

40 Liverpool St Ingleburn, NSW 2565

P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**

P: (03) 9768 3307

**NEWCASTLE**

P: (02) 4964 8436

**ACT**

P: 0411 094 945

**QUEENSLAND**

P: (07) 3556 1235

**NORTHERN TERRITORY**

P: 0429 771 810

**TASMANIA**

P: (03) 6423 4900