



PRODUCT DATA SHEET

ATLANTIC FSP 20 5W-20

Product Description:

Atlantic FSP 20 Fuel Saver 5W-20 is a high performance full synthetic low viscosity Fuel Saver Engine Oil. FSP 20 has been developed using the latest performance additives and Full Synthetic Base Stocks designed to provide superior fuel saving performance. FSP 20 advanced full synthetic motor oil is recommended for all types of modern petrol vehicles, including high-performance turbocharged, supercharged, variable timing, multi-valve fuel injected and Gasoline Direct Injection (GDI) engines found in passenger cars and SUVs. FSP 20 is not recommended for Diesel Engines.

Features and Benefits:

- Promotes quick oil circulation during cold starting
- Meets the latest API SP and ILSAC GF-6 specifications
- Premium wear protection
- Protects against engine sludge
- Maximises fuel economy
- Biofuel compatibility (E10 & E85)
- Designed for use in Turbo-charged & non turbo-charged Gasoline Direct Injection (TGDI) engines
- Suitable for use in petrol-electric (Hybrid) vehicles



Typical Data:

Test Description	Units	Results
Density @ 15°C	kg/L	0.851
Viscosity, Kinematic @ 40°C	cSt	45.9
Viscosity, Kinematic @100°C	cSt	8.5
Viscosity Index	-	164
Total Base Number (TBN)	mgKOH/g	7.7
Cold Cranking Viscosity	mPa.s	3700
Calcium	Wt.%	0.14
Zinc	Wt.%	0.09
Phosphorus	Wt.%	0.08

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	PFSP5201
20 Litre	PFSP5202
60 Litre	PFSP5203
205 Litre	PFSP5204
1000 Litre	PFSP5205



Specifications/ Performance Levels:

- **SAE Viscosity:** 5W-20
- **API:** SP Resource Conserving
- **ILSAC:** GF-6A
- **Chrysler:** MS-6395
- **Ford:** M2C945-A, M2C945-B1, M2C930-A, M2C960-A1



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900