



PRODUCT DATA SHEET

ATLANTIC GEAREX 85W-140

Product Description:

Atlantic Gearex 85W-140 is an extreme pressure multipurpose gear oil formulated with highly refined base stocks and a superior sulfur/ phosphorous additive pack. It provides outstanding protection to hypoid, spiral and helical gears under high shock loads like those used in differentials, transaxles, gearboxes and transfer cases. It can also be used in a wide range of heavy commercial, farm, earthmoving and industrial applications where a hypoid extreme pressure lubricant is required.

Features and Benefits:

- Suitable for use in gearboxes, transaxles, differentials and transfer cases.
- Superior corrosion protection
- Premium shock load protection
- Thermal stability
- Excellent film strength
- Fully compatible with seals and gaskets



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.904
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	384
Viscosity, Kinematic @ 100°C	ASTM D 445	cSt	28.5
Viscosity Index	ASTM D 2270	-	102
Pour Point	ASTM D 97	°C	-18
Flash Point	ASTM D 93	°C	22
Brookfield Viscosity @ -40°C	ASTM D 2983	cP	-

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

Specifications/ Performance Levels:

- **SAE Viscosity:** 85W-140
- **SAE:** J2360
- **API:** GL-5, MT-1
- **MACK:** GO-J
- **MIL-L-2105D**

PACK SIZE	PRODUCT CODE
5 Litre	AGM85141
20 Litre	AGM85142
60 Litre	AGM85143
205 Litre	AGM85144
1000 Litre	AGM85145



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900