



# SAFETY DATA SHEET

## ATLANTIC GEAREX FULL SYNTHETIC 75W-90

Version 1.0

Issue Date: 14/08/2019

Issued by Atlantic Lubricants Pty. Ltd.

### 1. IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND COMPANY

**Product Name** : Atlantic Gearex Full Synthetic 75W-90  
**Use** : Gear Oil  
**Product Code** : AGS7590  
**Company Name** : Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)  
**Address** : 40 Liverpool Street Ingleburn NSW 2565  
**Telephone/ Fax No** : Tel: (02) 9829 7555 Fax: (02) 9829 4555  
**Web** : www.atlanticoil.com  
**Emergency Telephone** : (02) 9829 7555  
Poisons Information Centre (Aust. 13 11 26)  
**Other Product Information** : (02) 8706 3240

### 2. HAZARD(S) IDENTIFICATION

**Classification of the mixture** : Classified as hazardous under GHS for Australia criteria  
**Hazard Classification** : Skin Sensitisation Category 1B  
Eye Irritation Category 2A  
Skin Irritation Category 2  
**Signal Word** : **Warning**  
**Pictograms** :



**Hazard Statements:** **H317** May cause an allergic skin reaction  
**H319** Causes serious eye irritation  
**H315** Causes skin irritation

**Additional Hazards** **H411** Toxic to aquatic life with long lasting effects



# SAFETY DATA SHEET

## 2. HAZARD(S) IDENTIFICATION

(Continued)

### Precautionary Statements:

**Prevention:** P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves and eye protection.

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

**Disposal:** P501 Dispose of container and used or unused contents as hazardous waste.

**Poisons Schedule** : Not Scheduled

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

(IP 346 DSMO extract <3%) with Proprietary additives.

COMPONENT	%(w/w)	CAS NUMBER
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	1-10%	Not available
Polysulfides, di-tert-Butyl	1-10%	68937-96-2
N-Tallow-1,3-Diaminopropane	<1%	61791-55-7
Bis(2-ethylhexyl) hydrogen phosphate	<1%	298-07-7
Amines, tallow alkyl	<1%	61790-33-8
Other ingredients classified as not hazardous, or at levels not requiring classification according to Safe Work Australia	Balance	-

## 4. FIRST AID MEASURES

### Description of necessary first aid measures

**Eye** : If contact with the eye(s) occurs, wash with copious amounts of water, holding eyelids(s) open. Continue flushing for at least 15 minutes. Remove contact lenses, if present and easy to do so. Take care not to rinse contaminated water into the non-affected eye. If irritation develops and persists, seek medical attention.

**Inhalation** : Remove the source of contamination or move the victim to fresh air. Seek medical attention if symptoms occur.

**Ingestion** : Do NOT induce vomiting. Immediately wash out mouth with water. Get medical attention if symptoms occur.



# SAFETY DATA SHEET

## 4. FIRST AID MEASURES

(Continued)

**Skin** : Remove contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. If irritation or rash develops, seek medical attention. Ensure contaminated clothing is washed separately by a commercial laundry before re-use, or discard. Do not take contaminated clothing home due to risk of allergic skin reaction by children or other people.

**Notes to physician** : Treat symptomatically with supportive care.

For further information contact Poisons Information Centre (Aust. 13 11 26)

## 5. FIRE FIGHTING MEASURES

**Extinguishing Media** : Carbon dioxide, foam or dry chemical. Do NOT use water jets. Use water spray to cool fire exposed containers.

**Specific Hazards** : C2 Combustible liquid.  
Fire-exposed container may rupture/explode.

**Hazards From Combustion Products** : Under fire conditions this product may emit toxic and/or irritating fumes including oxides of carbon.

**Precautions in Connection with Fire** : Self-Contained Breathing Apparatus (S.C.B.A) and full protective firefighting clothing.

## 6. ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible, contain the spill. Place inert, non-combustible, absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container.

Dispose of in accordance with State, Local Government, EPA or related Regulations or Codes of Practice. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority

## 7. HANDLING AND STORAGE

**Handling** : Repeated or prolonged contact with this material should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene i.e. washing hands prior to eating, drinking or going to the toilet. If there is a risk of eye contact, then eye protection must be worn. Build-up of mists in the working atmosphere must be prevented. Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.



# SAFETY DATA SHEET

## 7. HANDLING AND STORAGE

(Continued)

**Storage** : C2 Combustible liquid for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids. Store in original packaging as approved by manufacturer or regulatory direction.

## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

**Exposure Limits** : An exposure standard has been established for this material:  
**OIL MIST, REFINED, MINERAL TWA 5mg/m<sup>3</sup>**  
by Safe Work Australia.  
This applies only when the oil is released to air as a fine spray and is not expected to occur under ordinary conditions of use.

**Respiratory Protection** : If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependent upon actual concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, selection. Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

**Eye Protection** : Safety glasses with side shields, or goggles is recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 – Personal Eye Protection Part 1: Eye and Face Protectors for Industrial Applications.

**Hand Protection** : Wear gloves of impervious material such as nitrile, neoprene or butyl. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

**Body Protection** : Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

**Engineering Controls** : Natural ventilation should be sufficient, however where vapours or mists are generated the use of a local exhaust ventilation system (drawing spray or mists away from workers breathing zone) is recommended.



# SAFETY DATA SHEET

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	:	Clear Amber/brown liquid
<b>Odour</b>	:	Mild
<b>Solubility in Water</b>	:	Not Soluble
<b>pH Value</b>	:	Not Provided
<b>Electrostatic Stability</b>	:	Not Provided
<b>Vapour Pressure</b>	:	Not Provided
<b>Vapour Density</b>	:	Not Provided
<b>Flash Point</b>	:	>200°C
<b>Ignition Temperature</b>	:	Not Provided
<b>Melting Point</b>	:	Not Provided
<b>Boiling Point</b>	:	Not Provided
<b>Specific Gravity@ 15°C</b>	:	0.865
<b>Kinematic Viscosity cSt @ 40°C</b>	:	94.0
<b>cSt @ 100°C</b>	:	15.4
<b>Pour Point</b>	:	Not Provided

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	:	Stable under normal conditions.
<b>Hazardous Polymerization</b>	:	Will not occur.
<b>Materials to Avoid</b>	:	Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	:	Thermal decomposition may result in the release of toxic and or irritating fumes including carbon monoxide and carbon dioxide, plus oxides of sulfur and phosphorous
<b>Hazardous Reaction</b>	:	Hazardous reaction with strong oxidising agents.
<b>Conditions to avoid</b>	:	Heat, direct sunlight, open flames or other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE HEALTH EFFECTS

<b>Toxicology Information</b>	:	No toxicity data is available for this material. Data for ingredients indicate that the mixture is not significantly toxic
<b>Inhalation</b>	:	May cause irritation to the mucous membrane and upper airways, where material is heated and is used in poorly ventilated areas. Symptoms may include headache, dizziness and nausea.
<b>Ingestion</b>	:	May cause irritation of the gastrointestinal system. Symptoms may include nausea, vomiting and diarrhoea.



# SAFETY DATA SHEET

## 11. TOXICOLOGICAL INFORMATION

(Continued)

- Skin** : Causes irritation in contact with the skin, which may result in redness and itchiness, possibly leading to dermatitis. Repeated or prolonged exposure may lead to an allergic skin reaction and sensitisation to similar materials. Allergic reaction may develop long after initial exposure.
- Eye** : Causes irritation in contact with the eyes which could result in redness, stinging and tearing.

### CHRONIC HEALTH EFFECTS

- Chronic Effects** : Prolonged or repeated contact with this material may result in skin sensitisation leading to allergic skin reactions including dermatitis.

### OTHER INFORMATION

Used oils and greases may contain harmful impurities and contaminants that can accumulate during usage. Frequent or prolonged contact with all types and makes of used oil and grease must therefore be avoided.

## 12. ECOLOGICAL INFORMATION

- Ecotoxicity** : Harmful to aquatic life with long lasting effects.
- Persistence /Degradability** : Not expected to be readily biodegradable.
- Mobility** : Floats on water. Will be absorbed by earth.
- Bioaccumulation** : May bioaccumulate.
- Environmental Protection** : Prevent this material from entering the environment.

## 13. DISPOSAL CONSIDERATIONS

Do not dispose down drains or to soil or landfill.  
Dispose of waste according to state E.P.A. regulations. Use a licensed waste contractor and assure conformity with all applicable regulations.



# SAFETY DATA SHEET

## 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

**U.N. NUMBER** : None Allocated  
**PROPER SHIPPING NAME** : None Allocated  
**DG CLASS** : None Allocated  
**SUBSIDIARY HAZARD** : None Allocated  
**HAZCHEM CODE** : None Allocated  
**PACKING GROUP** : None Allocated

## 15. REGULATORY INFORMATION

**POISONS SCHEDULE** : Not scheduled

## 16. OTHER INFORMATION

**REFERENCES** : AS/NZS 1715 - Use and maintenance of Respiratory Protective Devices.  
AS/NZS 1716 - Respiratory Protective Devices.  
AS/NZS 1337 - Personal eye protection Part 1: Eye and face protectors for occupational applications.  
AS/NZS 2161.1 - Occupational protective gloves.  
AS 1940 - The storage and handling of flammable and combustible liquids.

### CONTACT

For information concerning details on this Safety Data Sheet contact Atlantic Technical Help Line on (02) 8706 3240.

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Atlantic accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS. A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

End of Safety Data Sheet