



# PRODUCT DATA SHEET

## ATLANTIC GEAREX LS140

### Product Description:

Atlantic Gearex LS140 is an extreme pressure multipurpose gear oil formulated with highly refined base stocks and a superior extreme pressure additive pack. It provides outstanding protection to hypoid, spiral and helical gears under high shock loads like those used in conventional and limited slip differentials. It can also be used in a wide range of heavy commercial, farm, earthmoving and industrial applications where a hypoid extreme pressure lubricant is required.

### Features and Benefits:

- Designed for use in conventional & limited slip differentials
- Anti-shudder
- Premium shock load protection
- Thermal stability
- Superior corrosion protection
- Excellent film strength
- Fully compatible with seals and gaskets



### Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.908
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	380
Viscosity, Kinematic @100°C	ASTM D 445	cSt	29
Viscosity Index	ASTM D 2270	-	105
Pour Point	ASTM D 97	°C	-18
Brookfield Viscosity @ -40°C	ASTM D 2983	cP	-

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

**HEAD OFFICE - SYDNEY**  
40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**  
P: (03) 9768 3307

**NEWCASTLE**  
P: (02) 4964 8436

**ACT**  
P: 0411 094 945

**QUEENSLAND**  
P: (07) 3556 1235

**NORTHERN TERRITORY**  
P: 0429 771 810

**TASMANIA**  
P: (03) 6423 4900



# PRODUCT DATA SHEET

## Specifications/ Performance Levels:

- **SAE Viscosity:** 140
- **SAE:** J2360
- **API:** GL-5, MT-1, PG-2
- **MACK:** GO-J
- **MIL-L-PRF-2105E**

PACK SIZE	PRODUCT CODE
5 Litre	AGL85141
20 Litre	AGL85142
60 Litre	AGL85143
205 Litre	AGL85144
1000 Litre	AGL85145



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

**HEAD OFFICE - SYDNEY**  
40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**  
P: (03) 9768 3307

**NEWCASTLE**  
P: (02) 4964 8436

**ACT**  
P: 0411 094 945

**QUEENSLAND**  
P: (07) 3556 1235

**NORTHERN TERRITORY**  
P: 0429 771 810

**TASMANIA**  
P: (03) 6423 4900