



PRODUCT DATA SHEET

ATLANTIC GEAREX RX80

Product Description:

Atlantic Gearex RX80 is a manual transmission fluid developed to provide easier gear changes over a wide temperature range. It's extreme pressure additives offer improved gear tooth and bearing durability by providing excellent film strength and superior protection. Atlantic Gearex RX80 is suitable for use in cars and light commercials manual transmissions and transfer cases where API GL-4 80W or 75W-80 is required.

Features and Benefits:

- Quieter transmission operations.
- Suitable for use in gearboxes and transfer cases.
- Easier low temperature shifting.
- GL-4 Extreme Pressure rating offers improved gear tooth and bearing durability.
- High wear stability – excellent film strength and protection during the life of the lubricant.
- Continued lubrication effectiveness over a broad range of operating temperatures.



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.885
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	73
Viscosity, Kinematic @ 100°C	ASTM D 445	cSt	10
Viscosity Index	ASTM D 2270	-	119
Pour Point	ASTM D 97	°C	-20
Brookfield Viscosity @ -40°C	ASTM D 2983	cP	-

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

Specifications/ Performance Levels:

- **SAE Viscosity:** 80
- **API:** GL-4

PACK SIZE	PRODUCT CODE
5 Litre	AGM80001
20 Litre	AGM80002
60 Litre	AGM80003
205 Litre	AGM80004
1000 Litre	AGM80005



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900