



PRODUCT DATA SHEET


ATLANTIC HY-LUBE HYDRAULIC FLUID

Product Description:

Atlantic HY-Lube hydraulic fluids are a range of universal zinc based anti-wear hydraulic fluids designed for the demanding performance requirements of today's hydraulic systems. Its blended with group II base oil and a premium additive package that provides outstanding protection against wear, rust, corrosion, oxidation and provides superior sludge and particle control. HY-Lube is recommended for hydraulic systems that utilise gear, vane and piston pumps and is safe for most seal and hose types. HY-Lube hydraulic fluid is available in the following ISO grades: 22, 32, 46, 68 & 100.

Features and Benefits:

- Excellent oxidation & hydrolytic stability
- Premium wear and oxidation protection
- Superior sludge and particle control
- Outstanding air release properties
- Excellent oil seal compatibility
- Zinc based Formulation



Typical Data:

Test Description	Method	Units	Results	Results	Results	Results	Results
ISO Viscosity Grade	-	-	22	32	46	68	100
Density @ 15°C	ASTM D 4052	kg/L	0.855	0.858	0.863	0.868	0.877
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	22.3	32.8	49.8	66	95
Viscosity, Kinematic @100°C	ASTM D 445	cSt	4.34	5.4	7.3	9.0	11.0
Viscosity Index	ASTM D 2270	-	101	97	106	111	100
Flash Point	ASTM D 93	°C	198	201	201	204	213
Pour Point	ASTM D 97	°C	-33	-27	-24	-20	-18

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	HY-LUBE 22 PRODUCT CODE	HY-LUBE 32 PRODUCT CODE	HY-LUBE 46 PRODUCT CODE	HY-LUBE 68 PRODUCT CODE	HY-LUBE 100 PRODUCT CODE
5 Litre	-	-	HYS46001	HYS68001	HYS10001
20 Litre	HYS22002	HYS32002	HYS46002	HYS68002	HYS10002
205 Litre	HYS22004	HYS32004	HYS46004	HYS68004	HYS10004
1000 Litre	HYS22005	HYS32005	HYS46005	HYS68005	HYS10005

Specifications/ Performance Levels:

- **ISO:** 22/ 32/ 46/ 68/ 100
- **Cincinnati Lamb:** (Milacron) P-68 (32), P-69 (68), P-70 (46)
- DIN 51524 part 2 (HLP)
- **Denison:** HF-0, HF-1, HF-2
- **Eaton:** (formerly Vickers) M-2950-S/ I-286-S
- ISO 11158
- **US Steel:** 126, 127



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900