



PRODUCT DATA SHEET

ATLANTIC LOG END SEALER

Product Description:

Atlantic Log End Sealer is a unique easy to apply wax based emulsion designed to retard moisture loss and reduce splitting of freshly sawn logs and timber boards. It has been specifically developed with superior stability and spraying characteristics allowing for excellent film uniformity and coverage with minimal dripping. Atlantic Log End Sealer can significantly reduce the number of off-cuts to increase production and marketable yield.

Features and Benefits:

- **Good Spray ability** enables easy, uniform application with brush, roller or high pressure sprayer without problems of tip and filter blockages.
- **High concentration of solids** provides good coverage and film thickness in one application.
- **Drip reduction formulation** specifically designed for vertical surfaces to reduce waste, mess and contamination of surrounding areas.
- **Superior stability** reduces the risk of separation in storage and subsequent risk of faulty application.
- **Fast drying time** provides improved operational flexibility in variable weather conditions with reduced chance of run-off due to unexpected rainfall.
- **Not classified as a Dangerous Good** enabling more flexible and convenient storage, handling and transportation.

Suggestions for Use:

Apply by spray, brush or roller to achieve a thick continuous film.

Do not dilute product.

Product standing for lengthy periods should be checked for any separation and agitated prior to use if required.

Product dries as a white film.

Clean Up:

Spray equipment should be adequately flushed with water immediately after use to avoid internal deposits of wax. Dried films may be cleaned easily with hot water, steam or mineral solvent.

Storage & Handling:

Atlantic Log End Sealer may be stored up to 12 months when kept between 4°C and 35°C.

Avoid exposure to air for prolonged periods as a solid film or crust may form on the product surface.

Gentle agitation or recirculation of product is recommended if stored for more than a few weeks.

Avoid generating foam in the tank by filling and returning recirculation below the surface. Only agitate gently when required.

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

Physical Properties:

Test Description	Result
Appearance	White Milky Liquid
Solids by Weight	30% min
Specific Gravity @ 20°C	0.98
Viscosity @ 20°C	Approx. 1000 cSt
Odour	Bland Waxy
Minimum Application Temperature	10°C
VOC	<1%



Health, Safety & Environment:

Atlantic Log End Sealer is not classified as a dangerous good. It is non-hazardous and considered of low risk to health if used according to appropriate industrial hygiene practices. Skin and eye contact should be avoided. Atlantic Log End Sealer is biodegraded by natural processes and poses a low risk to the environment.

PACK SIZE	PRODUCT CODE
20 Litre	LOGS0002
205 Litre	LOGS0004
1000 Litre	LOGS0005



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2024 Atlantic Lubricants Pty Ltd. All rights reserved.

7 November 2023

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900