



PRODUCT DATA SHEET

ATLANTIC MULTIPLEX EXTREME EP2 GREASE

Product Description:

Atlantic Multiplex Extreme EP2 Blue Grease is an extra high performance, high temperature multi-purpose grease formulated for use in wheel and other various bearings applications. It serves as a versatile grease suitable for a wide range of vehicles, including cars, trucks, buses, heavy construction and farm machinery. This grease excels in delivering outstanding performance in these applications.

When dealing with situations where water contamination is unavoidable or when operating at elevated temperatures, this grease will maintain effective lubrication. Its outstanding resistance to water washout ensures continued protection and minimizes the risk of rusting and corrosion. For ball joints with specific performance requirements, this grease is an excellent recommendation, ensuring minimal wear, torquing and complete rust protection.

Multiplex Extreme EP2 is also a definitive choice for industrial equipment operating under high-temperature conditions. Its exceptional ability to prevent scuffing and minimize wear, especially under heavy loads and shock loads, sets it apart from other multi-purpose greases.

Features and Benefits:

- Outstanding rust and corrosion protection.
- Excellent EP and anti-wear properties.
- Superior resistance to water wash-out.
- Excellent adhesion and cohesion properties reduce leakage.
- Superior oxidation and thermal stability extends grease life.
- Good pumpability and low-high temperature performance.
- Recommended for car & truck disc brakes, caravans and trailers.



Typical Data:

Test Description	Units	Results
Appearance	Visual	Blue & tacky
NLGI Classification	-	2
Thickener Type	-	Lithium Complex
Base Oil Viscosity @ 40°C	IP71	220 cSt min.
Dropping Point	IP132	260°C min.
Water Washout @ 38°C	IP215	3%
Oil Separation	IP121	3% max
Four Ball Weld Load	IP239	450 kg
Wear load index	-	62
Timken OK Load	IP386	20 kg/ 45 lbs
Worked Penetration (60 Strokes)	IP50	265 - 295
Operating Temperature Range	-	-20°C to +190°C

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
450 gm	GRSEEP21
2.5 kg	GRSEEP22
20 kg	GRSEEP23
55 kg	GRSEEP24
180 kg	GRSEEP25



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2024 Atlantic Lubricants Pty Ltd. All rights reserved.

23 November 2023

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900