



PRODUCT DATA SHEET

ATLANTIC PERFORMANCE PLUS 2T

Product Description:

Atlantic Performance Plus 2T is an Ultra High Performance Fully Synthetic two stroke engine oil. This product has been manufactured using Polyisobutylene (PIB) and Fully Synthetic Esters to produce an environmentally friendly (low smoke) two stroke oil for the most demanding applications.

Atlantic Performance Plus 2T is suitable for use in Ultra High Performance Motorcycles and Go-Karts especially those equipped with Rotax racing engines. The product meets the highest JASO specification of FD making it suitable for use in all Japanese Two Stroke Motor Cycles. Atlantic Performance Plus 2T has been engineered to meet Husqvarna Chain Saw requirements and has been designed to offer the highest protection in all industrial two stroke equipment.

Features and Benefits:

- Premium low ash, low smoke formulation
- Maximises engine life
- Protects against ring sticking
- Excellent anti scuff properties
- Tailored specifically for extreme applications
- Recommended for use in Rotax engines
- Designed for use in ultra-high performance Motorcycles and Go-Karts
- Perfect for home and industrial two stroke equipment



Typical Data:

Test Description	Units	Results
Density @ 15°C	kg/L	0.870
Viscosity, Kinematic @ 40°C	cSt	42
Viscosity, Kinematic @ 100°C	cSt	7.7
Viscosity Index	-	154
Flash Point (COC)	°C	92
Brookfield @ -25°C	cP	3620
Sulphated Ash	wt%	0.16

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	2TPP0001
20 Litre	2TPP0002



Specifications/ Performance Levels:

- **API:** TC
- ISO-L-EGD (**JASO** FD)
- ISO-L-EGC (**JASO** FC)
- Husqvarna 346 & 372 Chainsaw Engine Tests
- Rotax 253 Snowmobile Engines



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2024 Atlantic Lubricants Pty Ltd. All rights reserved.

7 November 2023

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900