



PRODUCT DATA SHEET

ATLANTIC PROGLIDE EXTREME 15W-40 CK-4

Product Description:

To meet the challenges of technological advancements in Diesel Engine design Atlantic Oil has developed Proglide Extreme 15W-40 CK-4. Proglide Extreme has been tested to meet the new Caterpillar Oil Aeration Test (COAT) critical for long drain intervals and the Mack T13 Lubricant Test essential to meet the new API CK-4 specification. It is designed to perform under the most arduous conditions where mission critical reliability is required. Proglide Extreme is suitable for heavy vehicle applications using Turbocharged and Naturally Aspirated engines employing emission control systems such as EGR, DPF DOC and or SCR NOx Reduction. Atlantic Proglide Extreme 15W-40 CK-4 is the prime recommendation for many OEM engine manufactures. Always refer to the Atlantic Lube Guide for the correct product application.

Features and Benefits:

- Backward compatible to previous categories such as API CJ-4
- Better shear stability
- Superior Sludge and viscosity increase control
- Improved piston deposit control
- Provides outstanding performance in reducing oxidation
- Designed for global aftertreatments systems
- Longer drain intervals



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.878
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	114
Viscosity, Kinematic @100°C	ASTM D 445	cSt	14.6
Viscosity Index	ASTM D 2270	-	131
Cold Cranking Viscosity	ASTM D 5293	cP @ -20°C	6590
Total Base Number (TBN)	ASTM D 2896	mgKOH/g	9.0
Flash Point	ASTM D 93	°C	220
Calcium	ASTM D 5185	ppm	242
Phosphorus	ASTM D 5185	ppm	1000
Zinc	ASTM D 5185	ppm	1100

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	DPG15401
20 Litre	DPG15402
60 Litre	DPG15403
205 Litre	DPG15404
1000 Litre	DPG15405



Specifications/ Performance Levels:

- **API:** CK-4/ SN
- **ACEA:** E9
- **Caterpillar:** ECF-3
- **Cummins:** CES 20086
- **Daimler:** MB 228.31
- **Detroit Diesel:** DDC 93K222
- **Deutz:** DQC III-18LA
- **Ford:** WSS-M2C171-F1
- **Mack:** EOS-4.5
- **MAN:** M 3775
- **MTU:** Cat 2.1
- **Renault:** RLD-3
- **Volvo:** VDS-4.5

OEM Approvals/ Licenses:

- **API:** Licensed
- **Cummins:** CES 20086
- **Detroit Diesel:** 93K222



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900