



# PRODUCT DATA SHEET

## ATLANTIC QIK-SHIFT SYN

### Product Description:

Atlantic Qik-Shift Syn is a synthetic multi-function multi-vehicle automatic transmission and power steering fluid that utilizes the latest fluid technology. It has been designed for use in passenger car, light commercial/ 4WD and heavy commercial applications and provides outstanding oxidation and thermal stability as well as superior anti-shudder performance, smoother shifting and longer transmission component service life.

Qik-Shift Syn is suitable for use in many 3, 4, & 5 speed automatic transmissions as well as manual transmissions, power steering units, transfer cases and hydraulic systems.

Qik-Shift Syn is NOT suitable for Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT). Always refer to the Atlantic Lube Guide for the correct product application.

### Features and Benefits:

- Fully synthetic offering long service intervals
- Smoother shifting
- Strong oxidation and thermal stability
- Increased wear protection
- Superior anti-shudder performance
- Improved power transfer
- Excellent anti-rust and corrosion protection
- Suitable for use in manual transmissions, power steering & hydraulic applications where a Dexron II/ III type ATF is required.



### Typical Data:

Test Description	Method	Units	Results
Appearance	Visual		Red
Density @ 15°C	ASTM D 4052	kg/L	0.849
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	34.2
Viscosity, Kinematic @100°C	ASTM D 445	cSt	7.15
Viscosity Index	ASTM D 2270	-	179
Flash Point (COC)	ASTM D 92	°C	236
Brookfield Viscosity @ -40°C	ASTM D 2983	cP	17,210

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

#### HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

#### VICTORIA

P: (03) 9768 3307

#### NEWCASTLE

P: (02) 4964 8436

#### ACT

P: 0411 094 945

#### QUEENSLAND

P: (07) 3556 1235

#### NORTHERN TERRITORY

P: 0429 771 810

#### TASMANIA

P: (03) 6423 4900



# PRODUCT DATA SHEET

## Specifications/ Performance Levels:

- **Aisin Warner:** JWS 3309
- **Allison:** C-3, C-4
- **Audi:** G 055 025 A2, G 052 990
- **BTR:** 5M-52, 95LE
- **BMW:** P/N 83 22 0 024 249/359 (ETL8072B), 83 22 0 026 922 (ETL7045E)
- **CAT:** TO-2
- **Chrysler:** ATF+, +2, +3 (MS 7176E), +4 (MS 9602)
- **Chrysler/Dodge:** MOPAR AS 68 RC
- **Esso:** LT 71141
- **Ford:** MERCON®, FNR5, M2C138-CJ, M2C166-H, M2C195-A, M2C922-A1, M2C924-A
- **Fuso:** ATF-II, ATF-SPIII, ATF A-4
- **GM:** Type A Suffix A, DEXRON®-II, -IID, -IIE, -IIIG, -IIIH, TASA, P/N 9986195, HN 2414
- **Hino:** Blue Ribbon ATF
- **Honda:** ATF Ultra II, ATF-Z1 (except in CVTs)
- **Hyundai:** SP-III, ATF RED 1, RED 1K
- **Isuzu:** Besco ATF-II, ATF-III
- **Jaguar:** ATF 3403 M115, JLM 20238,
- **JASO:** M315-2013 1A, M315-2013 2A
- **Jeep:** ATF+3, +4
- **Kia:** ATF SP-II, SP-III, RED 1, RED 1K
- **Mazda:** ATF D-II, M-III, M-V, F-1, S-1, N-1, 3317
- **Mercedes Benz:** 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
- **Mitsubishi:** Dia Queen AW, SP-II, SP-III, SK, J2
- **NAG 1** (Chrysler, Jeep, Cherokee)
- **Nissan:** Matic C, D, J, K
- **Peugeot:** AL-4
- **Porsche:** P/N 000 043 205 28, 999 917 547 00 (A2)
- **Renault:** DP-0
- **Saab:** 93 165 147
- **Shell:** 3403, M115, LA 2634
- **Subaru:** ATF, ATF HP
- **Suzuki:** ATF 2326, 2384K, JWS 3309, 3314, 3317
- **Texaco:** 7045-E, 8072B, N402
- **Toyota:** ATF D-II, D-III, T-III, T-IV, P/N 888681015
- **Vickers:** M2950-S, I-286-S
- **Volvo:** CE 97340
- **VW:** TL 521 62, G 052 162 (-A1, -A2), G-055-025 A2, G 052 990
- **ZF:** TE-ML 05L, 09, 11A, 11B, 21L



PACK SIZE	PRODUCT CODE
5 Litre	TQSS0001
20 Litre	TQSS0002
60 Litre	TQSS0003
205 Litre	TQSS0004



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2024 Atlantic Lubricants Pty Ltd. All rights reserved.

7 November 2023

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

**HEAD OFFICE - SYDNEY**  
40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**  
P: (03) 9768 3307

**NEWCASTLE**  
P: (02) 4964 8436

**ACT**  
P: 0411 094 945

**QUEENSLAND**  
P: (07) 3556 1235

**NORTHERN TERRITORY**  
P: 0429 771 810

**TASMANIA**  
P: (03) 6423 4900