



# PRODUCT DATA SHEET

## ATLANTIC SUPER OUTBOARD

### Product Description:

Atlantic Super Outboard is a low smoke marine oil specifically designed for water cooled modern 2-stroke outboard engines. It delivers excellent performance, through superior lubrication and deposit control and it's ashless additives and increased detergent design helps keep piston rings from sticking promoting smooth and efficient engine operation. Atlantic Super Outboard meets the requirements of the National Marine Manufacturer's Association (NMMA) TC-W3 specification and is suitable for use in oil injected systems and premix applications.

Always refer to the Atlantic Lube Guide for the correct lubricant application.

### Features and Benefits:

- Provides excellent lubrication and deposit control
- Protects against piston scuffing and pre-ignition issues
- Reduces engine corrosion
- Minimises plug fouling
- Suitable for use in pre-mix and oil injection systems
- Provides smooth and efficient engine operation
- Mixes easily with fuel for premix applications



### Typical Data:

Test Description	Units	Results
Colour	Visual	Amber
Density @ 15°C	kg/L	0.871
Viscosity, Kinematic @ 40°C	cSt	51.93
Viscosity, Kinematic @100°C	cSt	8.51
Viscosity Index	-	139
Total Base Number (TBN)	mgKOH/g	5.16
Ash	% wt.	<0.001
Pour Point	°C.	-33
Flash Point	°C.	103

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

#### HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

#### VICTORIA

P: (03) 9768 3307

#### NEWCASTLE

P: (02) 4964 8436

#### ACT

P: 0411 094 945

#### QUEENSLAND

P: (07) 3556 1235

#### NORTHERN TERRITORY

P: 0429 771 810

#### TASMANIA

P: (03) 6423 4900



# PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	OUTTCW31
20 Litre	OUTTCW32
205 Litre	OUTTCW34

## Specifications/ Performance Levels:

- **NMMA:** TC-W3



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

8 June 2022

**ATLANTIC LUBRICANTS PTY LTD** ABN 67 088 335 059

**HEAD OFFICE - SYDNEY**

40 Liverpool St Ingleburn, NSW 2565  
P: (02) 9829 7555

[atlanticoil.com](http://atlanticoil.com)

**VICTORIA**

P: (03) 9768 3307

**NEWCASTLE**

P: (02) 4964 8436

**ACT**

P: 0411 094 945

**QUEENSLAND**

P: (07) 3556 1235

**NORTHERN TERRITORY**

P: 0429 771 810

**TASMANIA**

P: (03) 6423 4900