



PRODUCT DATA SHEET

ATLANTIC SUPERTRONIC 15W-40 CI-4

Product Description:

Atlantic Supertronic 15W-40 CI-4 is a modern diesel engine oil designed for heavy duty applications. It has been blended from hydrocracked base stocks and a premium additive package. Supertronic 15W-40 CI-4 is suitable for turbocharged and naturally aspirated engines providing superior soot dispersing additives to ensure consistent lubricant viscosity throughout the service interval. It is suitable for servicing most light/ heavy duty on & off road vehicles, earthmoving machinery, agricultural tractors as well as industrial equipment. Supertronic 15W-40 CI-4 is however not recommended for diesel engines fitted with exhaust emission reduction systems such as DPF, CPF, DOC and or SCR. Always refer to the Atlantic Lube Guide for correct product application.

Features and Benefits:

- Premium engine protection
- Superior Sludge and viscosity increase control
- Provides outstanding performance in reducing oxidation
- Improved piston deposit protection
- Mid ash formulation minimises combustion deposits
- Suitable for use where API: CH-4, CG-4 or CF-4 is specified



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.878
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	113
Viscosity, Kinematic @100°C	ASTM D 445	cSt	14.9
Viscosity Index	ASTM D 2270	-	136
Cold Cranking Viscosity	ASTM D 5293	cP @ -20°C	-
Total Base Number (TBN)	ASTM D 2896	mgKOH/g	10.3
Flash Point	ASTM D 93	°C	212
Pour Point	ASTM D 97	°C	-39
Sulfated Ash	ASTM D 874	% wt.	1.39

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY
40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA
P: (03) 9768 3307

NEWCASTLE
P: (02) 4964 8436

ACT
P: 0411 094 945

QUEENSLAND
P: (07) 3556 1235

NORTHERN TERRITORY
P: 0429 771 810

TASMANIA
P: (03) 6423 4900



PRODUCT DATA SHEET

PACK SIZE	PRODUCT CODE
5 Litre	DST15401
20 Litre	DST15402
60 Litre	DST15403
205 Litre	DST15404
1000 Litre	DST15405

Specifications/ Performance Levels:

- **API:** CI-4/ SL
- **ACEA:** E7
- **Allison:** C4
- **Caterpillar:** ECF-2, ECF-1A
- **Cummins:** CES 20078
- **Daimler:** 228.3
- **Detroit Diesel:** DDC 93K215
- **Deutz:** DQC III-10
- **Global:** DHD-1
- **JASO:** DH-1
- **Mack:** EO-M Plus, EO-N
- **MAN:** M 3275
- **MTU:** Category 2
- **Renault:** RLD-2
- **Volvo:** VDS-3



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2024 Atlantic Lubricants Pty Ltd. All rights reserved.

7 November 2023

ATLANTIC LUBRICANTS PTY LTD ABN 67 088 335 059

HEAD OFFICE - SYDNEY

40 Liverpool St Ingleburn, NSW 2565
P: (02) 9829 7555

atlanticoil.com

VICTORIA

P: (03) 9768 3307

NEWCASTLE

P: (02) 4964 8436

ACT

P: 0411 094 945

QUEENSLAND

P: (07) 3556 1235

NORTHERN TERRITORY

P: 0429 771 810

TASMANIA

P: (03) 6423 4900